

SC-62-0210-0001-99

SmartCell Wireless Remote Indicator

Overview

The SmartCell wireless remote indicator is quick and easy to install and offers individual addressing at the SmartCell control panel.

Features include red fire indication LED, bidirectional 868 MHz communication and an anti-tamper locking mechanism.

This device is third party certified and compatible with the full SmartCell product range.



Details

- Fully wireless
- Quick and easy to install
- Red fire indication LED
- Unique design
- Inbuilt locking mechanism

SC-62-0210-0001-99

SmartCell Wireless Remote Indicator

Technical specifications

General

Wireless frequency	868 MHz
--------------------	---------

Electrical

Power supply type	Batteries
Batteries	3 x ER14505M 3.6 V lithium thionyl chloride batteries (Fanso or Titus)
Power consumption	1.46 W max.
Operating voltage	2.7 to 3.65 VDC
Current consumption	0.1 to 400 mA

Physical

Physical dimensions	110 x 39 mm (Ø x D)
Colour	White
Mounting type	Wall mount
Mounting base	Wireless

Environmental

Vandal proof	Yes
Operating temperature	-10 to +55 °C
Storage temperature	-10 to +30 °C (with batteries)
Relative humidity	0 to 95% noncondensing
Environment	Indoor
IP rating	IP21C

Regulatory

Compliance	CE
Certification	CPR
Standards	EN54-13 EN54-25



As a company of innovation, Carrier Fire & Security reserves the right to change product specifications without notice. For the latest product specifications, visit firesecurityproducts.com online or contact your sales representative.

Last updated on 5 May 2023 - 10:37